



7200 Series General Specifications:

- Flat Belt and Cleated Belt
- Loads up to 60 lbs. (27 Kg)
- Lengths up to 18' (5,486)
- Widths up to 18" (457)
- **CE** Models Available

7300 Series General Specifications:

- Flat Belt and Cleated Belt
- Loads up to 60 lbs. (27 Kg)
- Lengths up to 18' (5,486)
- Widths up to 18" (457)
- **CE** Models Available

Applications:

- Packaging
- Automated and Manual Assembly
- Sortation
- Testing and Inspection
- Curing, Cooling, Heating & Cleaning
- Clean Room



V-Guided Belts



**Quick Release
Rack & Pinion Tension**



**High Pressure
Bearing Options**

AquaPruf[®] SERIES INDEX

7200 Series Flat Belt End Drive 170
 7200 Series Cleated Belt End Drive 172
 7300 Series Flat Belt End Drive 174
 7300 Series Cleated Belt End Drive 176
 Profiles 178
 Belting 179
 Gearmotor Mounting Packages 182
 Gearmotors 186
 Support Stands 192
 Performance Charts / Data 194

CLEANING / APPLICATION FACTORS

Conveyor Type	Cleaning Method*			Type of Cleaning Agent**				Environment***	
	Wipe Down	Low Pressure Wash Down	High Pressure Wash Down	Water	Soap and Water	Diluted Bleach or Alcohol	Foaming Chlorine Cleaner	Dry	Wet
7200	X	X		X	X			X	X
7300	X	X	X	X	X	X	X	X	X

*Low Pressure Wash Down - conveyor belts and frames are hosed down with 100 psi or less liquid (garden hose pressure)

High Pressure Wash Down - conveyor belts and frames are hosed down with 100 - 1500 psi liquid

**This refers to the compatibility of the frame and bearing materials only. Belt types must be checked independently for chemical compatibility.

***Wet applications reduce conveyor load capacity.