

3200 SERIES

HEAVY DUTY BELT CONVEYORS EXTRUDED ALUMINUM



General Specifications:

- iDrive, Flat Belt End Drive, Cleated Belt End Drive, and Center Drive models
- 3" (76mm) diameter head and tail pulleys
- Widths: 3.75" (95 mm) to 48" (1,219 mm)
- Lengths: 3' (914 mm) to 99' (30,175 mm)
- Loads up to 1,000 lbs (455 kg)
- Sealed Bearings
- CE models available

Applications:

- Part Transfers
- Part Accumulation
- Precision Part Movement
- Part Incline / Decline Routing (Z-Frame)
- Part Handling and Positioning
- Automated and Manual Assembly



**V-Guided
Belt Tracking**



**Wide
Widths**



**Rack and Pinion
Belt Tensioning**



**Adjustable
Angles**

3200 iDRIVE	78
FLAT BELT END DRIVE	80
FLAT BELT CENTER DRIVE	82
CLEATED BELT END DRIVE	84
Z-FRAME FLAT BELT END DRIVE	86
Z-FRAME FLAT BELT CENTER DRIVE	88
Z-FRAME SIDEWALL CLEATED BELT END DRIVE	90
Z-FRAME STANDARD CLEATED BELT END DRIVE	92
PROFILES	94
BELTING	95
GEARMOTOR MOUNTING PACKAGES	98
GEARMOTORS	102
SUPPORT STANDS	113
ACCESSORIES	118
PART NUMBER REFERENCE	123