



Specifications:

- Load up to 1000 lbs.* (455 Kg)
- Belt Speeds up to 368 ft/min. (112 M/min)
- Belt widths: 3.75" (95) to 24" (610)
- Conveyor lengths: 4' (1,219) to 99' (30,175)
- 16" (406) of belt take-up
- 6" (152) diameter drive pulley turns approximately, 18.8" (479) of belt per revolution
- Metric fasteners
- CE Models available
- Reversing reduces load capacity by 33%
- Order Gearmotor separately

Note: Conveyors wider than 40" (1,016) require V-Guide belt tracking

Features/Benefits:

- Quick 15 minute belt change - NEW!
- Center Drive module frees up both ends of conveyor for operator and machine interface
- The Center Drive Module can be easily repositioned along the length of the conveyor
- Maintenance free pneumatic belt tensioner maintains uniform belt tension (Manual spring tension available)
- Steel nitrite coated head plates eliminate painted end surfaces
- V-groove bedplate with guided belt provides positive belt tracking, even under demanding side load applications
- Non V-guided belts use our patented belt tracking cams, offering you the widest belt selection possible
- Strong, box-like construction resists damaging frame twists
- 16" of belt take-up extends conveyor belt life
- Stand mounting brackets and return belt rollers are easily re-positioned along the frame
- Special length conveyors to .12" (3) increments at standard price and delivery
- Special width conveyors to 2" (51) increments at standard price and delivery
- Conveyor load capacity depends on conveyor size, incline, motor position, accumulated loads and other factors

Conveyor load capacity depends on conveyor size, incline, motor position, accumulated loads and other factors.