



### Specifications:

- Load up to 400 lbs.\* (181 Kg)
- Belt Speeds up to 421 ft/min. (128 M/min)
- Belt widths: 3.75" (95) to 48" (1,219)
- Conveyor lengths: 3' (914) to 40' (12,192)
- 1.62" (41) of belt take-up on conveyors up to 20' long
- 3.24" (82) of belt take-up on conveyors over 20' long
- 3" (76) diameter drive pulley turns approximately 9.7" (246) of belt per revolution
- Metric fasteners
- **CE** Models available

**Note:** Conveyors wider than 40" (1,016) require V-Guide belt tracking

### Features/Benefits:

- Quick 5 minute belt change
- Rack and pinion belt tensioning for fast, accurate single point belt tensioning
- Steel nitrite coated head plates eliminate painted surfaces
- V-groove bed plate with guided belt provides positive belt tracking, even under demanding side load applications
- Belt take-up indicator allows for quick reading of remaining belt life
- Strong, box-like construction resists damaging frame twist
- Stand mounting brackets and return belt rollers are easily re-positioned along the frame
- Special length conveyors to .12" (3) increments at standard price and delivery
- Special width conveyors to 2" (51) increments at standard price and delivery
- Conveyor load capacity depends on conveyor size, incline, motor position, accumulated loads and other factors

Conveyor load capacity depends on conveyor size, incline, motor position, accumulated loads and other factors.