



6200 Specifications:

- 11 gauge stainless steel roll formed frame
- Sealed Bearings
- Belt widths: 1.75" (44) to 12" (305)
- Conveyor lengths: 2' (610) to 24' (7,315)
- 1" (25) diameter head and tail pulleys
- The 1.25" (32) diameter drive pulley turns approximately 4.2" (107) of belt per revolution.
- 1.5" (38) bottom of frame to top of belt
- 12mm diameter integral drive shaft.
- Loads capacity up to 120 Lbs* (54 Kg)
- Reversing center drive belt direction reduces load capacity by 66%
- Belt speeds up to 264 ft/min. (81 M/min.)
- Metric fasteners
- Mild steel head and tail plates with black nitrite finish
- Motion sensor switch ready
- CE Models available

Features/Benefits:

- Center Drive models free up conveyor ends for machine or operator interface
- The Center Drive module can be easily repositioned along the length of the conveyor
- Streamlined design fits where other conveyors do not
- Low maintenance sealed bearings in both head and tail pulleys
- Lengths in .12" (4) increments
- Belt materials to match application requirements
- Quick clamp rail for easy mounting of bolt-on accessories
- V-Groove frame with guided belt ensures accurate tracking
- Durable .25" (6) thick bottom wiper

Conveyor load capacity depends on conveyor size, incline, motor position, accumulated loads and other factors.