



6200 Specifications:

- 11 gauge stainless steel roll formed frame
- Sealed bearings
- Belt widths: 1.75" (44) to 18" (457)
- Conveyor Lengths: 2' (610) to 18' (8,486)
- 1.5" (38) bottom of frame to top of belt
- 12mm diameter integral drive shaft
- The 1" (25) diameter drive pulley turns approximately 3.4" (86) of belt per revolution
- Load capacity up to 80 Lbs* (36 Kg)
- Belt speeds up to 255 ft/min. (78 M/min.)
- Metric fasteners
- Mild steel head and tail plates with black nitrile finish
- Motion sensor switch ready
- CE Models available

Features/Benefits:

- Wedge-Lok system for impact protection
- Streamlined design fits where other conveyors do not
- Quick 5 minute belt change for increased uptime
- Low maintenance sealed bearings in both head and tail pulleys
- Lengths in .12" (4) increments
- Belt materials to match application requirements
- Quick clamp rail for easy mounting of bolt-on accessories
- Rack and pinion design offers fast single point belt tensioning
- V-Groove frame with guided belt ensures accurate tracking
- Durable .25" (6) thick bottom wiper
- Optional spindles for "gang drive" applications
- Magnetic models available

** Gang Drive tail pulley requires periodic greasing.

Conveyor load capacity depends on conveyor size, incline, motor position, accumulated loads and other factors.