



7300 Specifications:

- Self-aligning stainless steel bearings with FDA approved Lubricant and high pressure resistant bearing cap
- 11 gauge stainless steel roll formed frame
- Belt widths: 1.75" (44) to 18" (457)
- Conveyor lengths: 2' (610) to 18' (8,486)
- 1.5" (38) bottom of frame to top of belt
- 12mm diameter integral drive shaft
- The 1.25" (32) diameter drive pulley turns approximately 4.25" (108) of belt per revolution
- 2' (610) minimum, 18' (8,486) maximum conveyor lengths
- Loads up to 60 Lbs* (27 Kg)
- Belt speeds up to 264 ft/min. (81 M/min.)
- Metric fasteners
- Complete stainless steel construction
- Washdown rated gearmotors and controls
- **CE** Models available

Features/Benefits:

- Wedge-Lok system for impact protection
- Pre-engineered conveyor and accessory solutions for fast delivery
- Streamlined design fits where other conveyors do not
- Quick 5 minute belt change for increased uptime
- 304 stainless steel frame, head and tail plates are polished to a #4 finish
- Quick clamp rail for easy mounting of bolt-on accessories
- Rack and pinion for fast single point belt tensioning
- V-Groove frame with guided belt ensures accurate tracking
- Optional 1/4" (6mm) thick bottom wiper
- A variety of FDA approved belting to meet application needs
- Lengths in .12" (3) increments
- Low profile, single piece frame for quick, easy cleaning

Conveyor load capacity depends on conveyor size, incline, motor position, accumulated loads and other factors.