



Specifications:

- Belt widths: 3.75" (95) to 48" (1,219)
- Conveyor lengths: 4' (1,219) to 40' (12,192)
- 1.62" (41) of belt take-up on conveyors up to 20' long
- 3.24" (82) of belt take-up on conveyors over 20' long
- Loads up to 400 lbs.* (181)
- Adjustable angle, 0°-35°
- Belt speeds to 421 ft/min (128 M/min)
- 3" (76) diameter drive pulley turns approximately 9.7" (246) of belt per revolution
- Metric fasteners

Note: Conveyors wider than 40" (1,016) require V-Guide belt tracking

Features/Benefits:

- Quick 5 minute belt change
- Adjustable angle frames conform to applications
- Rack and pinion belt tensioning for fast, accurate single point belt tensioning
- Steel nitrite coated head plates eliminate painted surfaces
- V-groove bed plate with guided belt provides positive belt tracking, even under demanding side load applications
- Strong, box-like construction resists damaging frame twist
- Stand mounting brackets and return belt rollers are easily re-positioned along the frame
- Special length conveyors to .12" (3) increments at standard price and delivery
- Special width conveyors to 2" (51) increments at standard price and delivery
- Conveyor load capacity depends on conveyor size, incline, motor position, accumulated loads and other factors

Conveyor load capacity depends on conveyor size, incline, motor position, accumulated loads and other factors.