



Features & Specifications

- Available on Dorner 2200 Series Conveyors
 - Also available on Dorner 3200 Series, AquaGard, and AquaPruf Conveyors. Contact factory for details
- Widths: 44 mm to 610 mm
- Aluminum extruded frame with T-Slot construction
- 48 mm frame height
- Sealed ball bearings
- V-Guided and Non V-Guided belt compatible
- Rack and pinion belt tensioning

Metal-Free Zone Specifications

- Engineered plastic metal free mid-section to install metal detector
- Size of the zone is determined by the metal detection unit being integrated
- Metal detector is to be specified and acquired separately
- Reference the conveyor specification sheet or www.dorner.com for additional details and specifications

Options & Accessories

- Standard support stands and guiding options
- Available with series standard mounting packages and gearmotors
- Multiple belt options available

2200 SERIES METAL-FREE ZONE CONVEYORS

Simplify Product Inspection with **Metal Detection Conveyors**

- Metal-Free Zone can be customized to match any metal detector
- Reliable inspection with UHMW and other nonmetal components in the metal detection zone
- Simple, low profile frame height easily slides into metal detector opening
- Compact frame to belt width maximizes use of detector opening
- Fabric or Modular Belt options depending on product type and application



Fabric or Modular Belt options



Also available on Dorner 3200 Series, AguaGard, and AguaPruf Conveyors











